

Customising sender and form footer

 Language: [Deutsch](#) · [English](#)

Customising sender and form footer

Maintain sender and form footer centrally via the language files of the Bundle.jar.

HOW-TO

ADMINISTRATOR

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Maintain sender & form footer centrally](#)
- [1. Extract Bundle.jar](#)
- [2. Edit sender & footer](#)
- [3. Repackage as Bundle.jar](#)
- [4. Deploy](#)
- [Related pages](#)

Maintain sender & form footer centrally

Sender and form footer are stored in the **language files** of the Bundle.jar (Bundle.properties, Bundle_de.properties, Bundle_en.properties). Advantage: central maintenance and regional specifics in one place.

1. Extract Bundle.jar

```
cd <BundlePlace>
jar xf <Nuclos-Home>/extensions/server/Bundle.jar
```

2. Edit sender & footer

Open Bundle.properties, select the appropriate language entry (e.g. German) for the sender and edit it. The form footer consists of 7 properties (footer.label...). Don't forget to save.

3. Repackage as Bundle.jar

```
cd <BundlePlace>
jar cvf <Nuclos-Home>/extensions/server/Bundle.jar .
```

4. Deploy

Run the installer again – only then are the features permanently available. Alternatively copy the JAR **additionally** to webapp/WEB-INF/lib and restart the server.

Related pages

Forms

Forms.

[Open](#)

Jasper extensions in Nuclos

Extensions.

[Open](#)

