

# Stop a high-CPU Oracle process

🌐 Language: [Deutsch](#) · [English](#)

## 🔧 Stop a high-CPU Oracle process

When an Oracle background process pins the CPU: detect it, kill the session and prevent it from returning.

HOW-TO

OPERATIONS

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

### On this page

- [1. Show active processes](#)
- [2. Get session data](#)
- [3. Kill the session](#)
- [Related pages](#)



### Context

These steps come from maintaining the old development VM and are very Oracle-specific. Use with care on production systems.

## 1. Show active processes

```
SELECT s.username, s.sid, s.osuser, t.sql_id, sql_text
FROM v$sqltext_with_newlines t, v$session s
WHERE t.address = s.sql_address AND t.hash_value = s.sql_hash_value
AND s.status = 'ACTIVE' AND s.username <> 'SYSTEM';
```

## 2. Get session data

```
SELECT inst_id, sid, serial# FROM gv$session WHERE sid = 133;
```

## 3. Kill the session

```
ALTER SYSTEM KILL SESSION '133,9,@1';
```

To prevent recurrence, remove the root cause (e.g. a problematic materialized view).

## Related pages

### Oracle SQLPlus tools (DE)

More SQLPlus queries.

[Open](#)

