

Transferring a data source to Nuclos

🌐 Language: [Deutsch](#) · [English](#)

🔧 Transferring a data source to Nuclos

Move SQL from the Jaspersoft designer into the Nuclos data source editor – incl. parameter and schema adjustments.

HOW-TO

APPLICATION DEVELOPER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Transfer a designer data source to Nuclos](#)
- [Steps](#)
- [Related pages](#)

Transfer a designer data source to Nuclos

A data source created in the [designer](#) must be transferred to the Nuclos data source editor (*Configuration* *Data sources* [Report and form](#)).

Steps

1. Create a new data source and set **name + description** (mandatory).
2. In the **SQL** tab click *edit statement* and paste the query from the designer.
3. Create a parameter for filtering. Syntax: `$intid` (integer), `'$Date'` / `'$String'` (date/text).
4. **Delete the schema name** – needed in the designer, not in Nuclos.
5. Check the syntax via the *test* icon, then save.

Server Regel (API-basiert) - Report & Formular "FormulRechnung - Details1004 - 1082 - DetailsReport & Formular - Neuein

ListeDetailsExtras

Test

Name

Formular Auftragsbeispiel

Beschreibung

Beispiel Datenquelle für einen Auftragsdatensatz

Modell

SQL

Vorschau

Statement wieder herstellen

Vorher:
"Statement bearbeiten" betätigen

Parameter...	Datentyp	Pflichtpara...
intid	Integer	

```
SELECT
a."intid" ,
a."strnummer",
a."dblvkbrutto",
a."dblvknetto",
a."dbleknetto",
a."dblmwst",
a."dblrabattnetto",
a."strrname",
a."strrpostfach",
a."strrstrassezusatz" ,
a."strrnamezusatz",
a."strrfirma",
a."strrstrasse",
l.strname "strland",
po.strort,
po.strplz

FROM
nuclos.t_eo_auftrag a
left outer join nuclos.t_eo_land l on l.intid = a.intid_strrland
left outer join nuclos.t_eo_postleitzahlen po on po.intid = a.intid_strrplzort

WHERE
a.intid = 0(intid) $intid
```

Transferred data source in the Nuclos editor.



Testing

Test the data source functionally in the **preview** tab (set the \$intid parameter to a value).

Related pages



Creating a data source in the designer

In the designer.

[Open](#)



Report and form

Nuclos data source.

[Open](#)