

Login

 Language: [Deutsch](#) · **English**

Login

How to start the Rich Client and log in to the system.

HOW-TO

USER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Start the client](#)
- [Log in](#)
- [Start the client with parameters](#)
- [Related pages](#)

Start the client

The Rich Client is started via the [Launcher](#) (address `nuclos://<server>:<port>/<instance>`).



No more Web Start

Since Java 11 there is no Java Web Start – use the [Launcher](#).



Nuclos start page.

Log in

The image shows a login dialog box for NUCLOS. It has a light grey background with the NUCLOS logo at the top. The form contains the following fields and controls: a "Benutzername" (Username) label followed by a text input field containing "nuclos"; a "Passwort" (Password) label followed by a text input field; an "Autologin" checkbox; and a "Region/Sprache" (Region/Language) label followed by a dropdown menu currently showing "Deutsch". At the bottom of the dialog are two buttons: "OK" and "Abbrechen" (Cancel).

Login dialog.

Enter user name, password and application server. Right after installation the user `nuclos` works without a password – set a password in the first session and create your own user.

- **Auto login:** logs in automatically; can be disabled via the system parameter `application.settings.client.autologin.allowed`.
- **Language/region:** choose the application language.

Start the client with parameters

From version 4.3 the start can be parameterised, e.g. to open a record directly:

```
nuclos://<host>:<port>/<instance>/app/webstart.jnlp?buid=<B0-uid>&pk=<record-id>
```

Alternatively by field value (`fuid + value`). If several records match, the result list opens.

Related pages



User interface

After login: the interface.

[Open](#)



Password

Change your password.

[Open](#)