

Colored rows

Language: [Deutsch](#) · [English](#)

Colored rows

Color list rows based on data – across clients via the **NuclosRowColor** attribute.

HOW-TO

LOW-CODE / DEVELOPER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Related pages](#)

To color rows in the list view, add an attribute **NuclosRowColor** to the BO (case-insensitive) and fill it with an HTML hex code (#RRGGBB) per record.



Dev

Order

Example

Matrix

Test

test

Textsearch

Q

Info

10020158 Test-Customer 1

10020154 Test-Customer 1

10020150 Test-Customer 1

10020148 Test-Customer 1

10020144 Test-Customer 1

10020140 Test-Customer 1

+

🗑️

🖨️

Processing

abschließen

abbrechen

Order number

10020158

Send order

Action

Send date

Customer

Test-Customer 1

Customer address

Order date

09/01/2015

Discount

Confirmation

Select file or drop file to upload

Order

Select file or drop file to upload

Position (4)

Article	Price	Quantity	Category
1004 Mouse	5,400.00	180.00	
1003 Notebook Pro	45,000.00	15.00	
1002 Text processor	2,003,000.00	10,015.00	
1001 Nuclos	0.00	15.00	

Colored rows in the list view.



Recommendation

Groovy rules for color logic no longer work in the Web Client. Implementation that works in both clients:

1. Add attribute **NuclosRowColor** (String).
2. Fill it as a **calculated attribute** via a DB function with the hex code (the logic belongs in the DB function, not in Groovy).
3. For the Rich Client a Groovy rule that only forwards the DB value suffices: `return <NUCLET>.<B0>.NuclosRowColor`; – the Web Client ignores it.

The Web Client does not show the attribute as a column but interprets it as the row color. Example DB function (MS SQL Server):

```
CREATE FUNCTION R0X7_CA_AP_ROWCOLOR(@id NUMERIC) RETURNS VARCHAR(255) AS
BEGIN
    DECLARE @val VARCHAR(255);
    DECLARE @free NUMERIC(9,2);
    DECLARE @used NUMERIC(9,2);
    select @free = min(bestand-reserviert) from R0X7_V_BESTANDSPLANUNG
        where intid_strauftragsposition = @id;
    select @used = dblmenge from R0X7_MESSEAUFRAGSPPOSITION where intid = @id;
    if (@free > (@used + 10)) select @val = '#01DF01';
    else if (@free > @used) select @val = '#F7FE2E';
    else select @val = '#FF0000';
    return @val;
END;
```

Related pages



List views

Columns & views.

[Open](#)



Custom CSS

More styling.

[Open](#)