

3. Login

🌐 Language: [Deutsch](#) · [English](#)

🔧 3. Login

Authenticate at the REST service – POST with JSON credentials, JSESSIONID cookie and logout via DELETE.

HOW-TO

DEVELOPER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Request](#)
- [Passing the session ID](#)
- [Logout](#)
- [Related pages](#)

Log in via **POST** to the root URL of the REST service (<http://localhost:8080/nuclos-war/rest/>). User name and password are passed as JSON.

Request

Fehler beim Rendern des Makros 'code': Ungültiger Wert für den Parameter 'com.atlassian.confluence.ext.code.render.InvalidValueException'

```
{"username": "nuclos", "password": ""}
```

Required headers:

Fehler beim Rendern des Makros 'code': Ungültiger Wert für den Parameter 'com.atlassian.confluence.ext.code.render.InvalidValueException'

Accept: application/json

Content-Type: application/json

The response is a JSON object with the entry links (e.g. boMetas, menu).

Passing the session ID

All services (except a few such as login) require a valid session ID – otherwise the service responds with HTTP **401 (Unauthorized)**. The session ID is passed as the cookie JSESSIONID=xxx.



sessionId header removed

In Nuclos 4.4.x/4.5.x the header sessionId was an alternative – from **4.6** it is **no longer** supported.

Logout

Same URL as login, via **DELETE** – invalidates the session ID (HTTP 200 if it was valid).

Related pages



4. Reading business objects (BO)

Read BOs.

[Open](#)



Example calls via shell

curl.

[Open](#)

