

Jaspersoft Studio installation

 Language: [Deutsch](#) · [English](#)

Jaspersoft Studio installation

Install Jaspersoft Studio 6.17.0 on Windows and Linux.

HOW-TO

APPLICATION DEVELOPER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [Download](#)
- [Windows](#)
- [Linux](#)
- [Related pages](#)

Download

The Jaspersoft Studio Community Edition is available on the Jaspersoft website (matching the Nuclos library, recommended: 6.17.0).

Windows

Download the Windows setup (.exe), run it and follow the installer steps.

Linux

Extract the archive into the target directory:

```
tar xfvz ~/<download>/TIB_js-studiocomm_6.17.0_linux_x86_64.tgz -C /home/<target>
```

Start via the Jaspersoft Studio file in the extracted folder. On first start a hidden .ireport folder with version-specific configurations is created in your home. Create a menu launcher via a jaspersoftstudio.desktop file in /usr/share/applications:

```
[Desktop Entry]
Encoding=UTF-8
Name=Jaspersoft Studio
Comment=Jaspersoft Studio
Exec="/<wo ist jaspersoft studio>/TIB_js-studiocomm_6.20.0/Jaspersoft Studio"
Icon="/<wo ist jaspersoft studio>/TIB_js-studiocomm_6.20.0/icon.xpm"
Terminal=false
Type=Application
Categories=Application;Development
StartupNotify=true
```



Tip for start-up issues

If the direct launch causes problems on Linux, the bundled runjss.sh in the studio directory helps (see linux.readme).

Related pages



Working with Jasper Studio

Overview.



First steps with Jasper Studio

First report.

Open

Open