

Jasper extensions in Nuclos

🌐 Language: [Deutsch](#) · [English](#)

🔧 Jasper extensions in Nuclos

Register fonts, scriptlets and barcode/QR libraries as server-side extensions in the Jasper classpath.

HOW-TO

APPLICATION DEVELOPER

UPDATED: JUL 2026

APPLIES TO NUCLOS 4.2026.X

On this page

- [What are Jasper extensions?](#)
- [1. Install the extension](#)
- [2. Register the extension in the classpath](#)
- [Related pages](#)

What are Jasper extensions?

Whenever you add an extension to your Jasper report – e.g. a font package, a [scriptlet library](#), a [barcode generator](#) or ZXing for [QR codes](#) – you must also register this server-side extension in Nuclos so the report can run.

1. Install the extension

Option A – via a nuclet: Configuration Nuclets, select the nuclet, add the JAR in the *Extensions* tab and tick *Server Extension?*.

Option B – in the server directory: create a folder `extensions/server` in the Nuclos instance directory, place the JARs there and **additionally** under `webapp/WEB-INF/lib` in Tomcat.

2. Register the extension in the classpath

For the JasperReports component to use the extension, register it via the parameter under *Administration Parameters*:

1. Parameter name: `nuclos.jasper.reports.compile.classpath.jars.byclasses`
2. Description: free text.
3. Value: **one class incl. package path** per extension, separated by a space or a new line.



Mandatory values

These two **mandatory values** must always be present, otherwise reporting will not work:
`net.sf.jasperreports.engine.JasperReport` `org.nuclos.server.report.api.JRNuclosDataSource`

ne Filter 1 Hauptlager E-Mail Queue - Ergebnis Bestellvorschlag Artikel Zahlungsfrist

Liste Details Extras

Lager

Datensatz 1/1

Report & Formular "Repe Auftragsbestaetigung_De Report Artikelstatistik Reporting - Ausführung - nuclos.jasp

Liste Details Extras

Name 1

Beschreib... 2

Wert 3

Classpath parameter in the administration.

Example value including ZXing (QR code):

```
net.sf.jasperreports.engine.JasperReport org.nuclos.server.report.api.JRNuclosDataSource com.google.zxing.
BarcodeFormat com.google.zxing.WriterException com.google.zxing.client.j2se.MatrixToImageWriter com.google.
zxing.common.BitMatrix com.google.zxing.qrcode.QRCodeWriter com.qrbarcode.QRCodeClass
```



Restart

After every change to the parameter a **server restart** is required.

Related pages



Scriptlets

Scriptlets.

[Open](#)



Embedding a barcode

Barcodes.

[Open](#)



QR codes in reporting

QR codes.

[Open](#)