

Beispielaufrufe per Shell

- [Login](#)
- [Neue Order anlegen](#)
- [Vorhandene Order ändern](#)
- [Order löschen](#)
- [Statuswechsel einer Order](#)
- [Report ausführen](#)
- [Logout](#)

Zur Veranschaulichung und als kleine Hilfe möchten wir hier ein paar Beispielaufrufe, die per Shell abgesetzt werden können, auflisten.

Um die Statements möglichst kurz zu halten sind größere JSON Inhalte in Dateien ausgelagert:

Datei	Geändert
Datei insert_order_2002.json	Juli 26, 2015 by Maik Stüker
Datei update_order_1012.json	Juli 26, 2015 by Maik Stüker
Datei update2_order_1012.json	Juli 26, 2015 by Maik Stüker

[Alle herunterladen](#)

Login

```
export JSESSIONID=`curl -X POST -d '{"username":"nuclos", "password":""}' http://localhost:8080/nuclos-war/rest -H "Accept:application/json" -H "Content-Type:application/json" | awk -v FS="\"" '{ print $4 }'`
```

Neue Order anlegen

Anhang [insert_order_2002.json](#)

```
curl -X POST -d @insert_order_2002.json http://localhost:8080/nuclos-war/rest/bos/example_rest_Order -H "Cookie:JSESSIONID=$JSESSIONID" -H "Content-Type:application/json" -H "Accept:application/json"
```

Vorhandene Order ändern

Anhang [update_order_1012.json](#)

- Attribut **node** wird gesetzt
- Unterformular **position** erhält einen neuen Eintrag und der Vorhandene wird geändert

```
curl -X PUT -d @update_order_1012.json http://localhost:8080/nuclos-war/rest/bos/example_rest_Order/40000305 -H "Cookie:JSESSIONID=$JSESSIONID" -H "Content-Type:application/json" -H "Accept:application/json"
```

Anhang [update2_order_1012.json](#)

- Attribute **node** wird geändert
- Unterformular **position**, ein Eintrag wird gelöscht

```
curl -X PUT -d @update2_order_1012.json http://localhost:8080/nuclos-war/rest/bos/example_rest_Order/40000305 -H "Cookie:JSESSIONID=$JSESSIONID" -H "Content-Type:application/json" -H "Accept:application/json"
```

Order löschen

order_1012

```
curl -X DELETE http://localhost:8080/nuclos-war/rest/bos/example_rest_Order/40000305 -H "Cookie: JSESSIONID=$JSESSIONID"
```

Statuswechsel einer Order

order_1011 nach Finished

```
curl -X GET http://localhost:8080/nuclos-war/rest/boStateChanges/example_rest_Order/40000302 /example_rest_ExampleorderSM_State_80 -H "Cookie: JSESSIONID=$JSESSIONID"
```

Report ausführen

```
# Anmelden und Token erhalten
AUTH_RESPONSE=$(curl -X 'POST' \
  'https://nucuclos.de/rest' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -d '{
    "username": "nuclos",
    "password": "n!12345"
  }')

# Extrahiere das Token aus der AUTH_RESPONSE
TOKEN=$(echo "$AUTH_RESPONSE" | jq -r '.sessionId')

curl -X 'POST' \
  'https://nucuclos.de/rest/reports/ssdfksdfkfjsafdj/execute' \
  -H 'accept: application/json' \
  -H 'Content-Type: application/json' \
  -H "Cookie: JSESSIONID=$TOKEN" \
  -d '{
    "printoutId": "org_nuclet_test_ExportPO",
    "name": "Export",
    "outputFormats": [
      {
        "outputFormatId": "org_nuclet_test_ExportPO_artikel",
        "name": "artikel",
        "selected": true
      },
      {
        "outputFormatId": "org_nuclet_test_ExportPO_vkpreis",
        "name": "vkpreis",
        "selected": true
      }
    ]
  }'
```

```
curl -X GET http://localhost:8080/nuclos-war/rest/boStateChanges/example_rest_Order/40000302 /example_rest_ExampleorderSM_State_80 -H "Cookie: JSESSIONID=$JSESSIONID"
```

Logout

```
curl -X DELETE http://localhost:8080/nuclos-war/rest -H "Cookie:JSESSIONID=$JSESSIONID"
```